Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G	
Product Code:	7029.160, 7029.161	
Page 1 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G
Other Names:	N/A
Recommended Use:	Paint/Drawing on Canvas, Paper, Wood, Porcelain
Supplier: ABN:	Rico Design GmbH & Co. KG
Street Address:	Industriestr. 19-23, D 33034 Brakel
Telephone Number:	05272-602-0
Emergency Telephone No:	+0086 20 87467206

2. HAZARDS IDENTIFICATION

Based on available information, the material is:

NON HAZARDOUS ACCORDING TO CLP (EU-GHS)

Hazard category:

N/A

Risk Phrases: (CLP (EU-GHS) C) Risk Phrase Number R R R R R

Safety Phrases: N/A (see Approved Criteria for CLP (EU-GHS) Safety Phrase Number S S S S S

Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLI	BINDER 470G
Product Code:	7029.160, 7029.161	
Page 2 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

3. COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS No.	Proportion	
Water Propylene glycol Mixture of 5-chloro-2-methyl-isothiazol-3(2H)-one and 2-methylisothiazol-3(2H)-one with magnesium chloride and magnesium nitrate	7732-18-5 57-55-6	52.4842 2.5000 0.0008	
Bronopo Acrylic Resin	52-51-7 <mark>9003-49-0</mark>	0.0150 45.0000	

4. FIRST AID MEASURES

For advice, contact Poisons Information Centre or a doctor.

(For each route of exposure provide indication of medical attention and special treatment needed including description of most important symptoms, acute and delayed)

Inhalation:	Remove patient to fresh air Keep warm and at rest, in a half upright position. Loosen clothing Seek medical attention if ill effects occur
Skin Contact:	Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water Seek medical attention if irritation persists
Eye Contact:	If substance has got into eyes, immediately wash out with water for at least 15 minutes . Contact physician
Ingestion:	If swallowed accidentally, do not induce vomiting and seek medical advice.
Note to Physician:	

Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G	
Product Code:	7029.160, 7029.161	
Page 3 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

5. FIRE FIGHTING MEASURES	
Hazards from combustion products:	Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2
Precautions for firefighters and special protective equipment:	Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes
Suitable extinguishing material	foam, carbon dioxide or dry agent

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:	Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.
Methods and materials for containment and clean up:	Absorb spillage in suitable inert material Place in appropriate container

7. HANDLING AND STORAGE

Precautions for safe handling: (including any incompatibilities)	Keep away from heat and sources of ignition Take precautionary measures against static discharges Equipment should be earthed Use explosion-proof electrical/ventilating/lighting//equipment. Use only non-sparking tools. Do not breathe aerosols or vapours. Ensure adequate ventilation Avoid contact with skin and eyes. Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection.
Conditions for safe storage:	Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children

Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G	
Product Code:	7029.160, 7029.161	
Page 4 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G	
Product Code:	7029.160, 7029.161	
Page 5 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National Exposure Standards:	N/A
Biological Limit Values:	N/A
Engineering Controls:	N/A
Personal Protective Equipment:	Take precautions to avoid contact with skin and eyes when handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Color Liquid
Odour:	No
pH:	7~9.5
Specific Gravity or Density:	1.15
Vapour Pressure:	N/A
Vapour Density:	N/A
Percent Volatiles:	N/A
Boiling Point Range:	100°C
Freezing/ Melting Point:	-8°C
Solubility:	Soluble in water
Flash Point	N/A
(include method detection):	
Flammability Limits:	N/A
Ignition Temperature:	N/A
Shelf Life:	2 years from date of manufacture (when stored as directed)
Other:	

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions to avoid:	Avoid overheating
Incompatible Materials:	Strong oxidising agent
Hazardous Decomposition	CO,CO2
Products: Hazardous Reactions:	No hazardous reactions known if used for its intended purpose

Brand & Product Name: ACRYLIC BINDER 235G, ACRYLBINDER 470G			
Product Code:	7029.160, 7029.161	7029.160, 7029.161	
Page 6 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015	

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<u>HEALTH EFFECTS</u>	
Ingestion:	may give rise to nausea, headaches and dizziness
Eye Contact:	Irritating to eyes
Skin Contact:	May cause irritation.
Inhalation:	N/Ă
Long term effects:	N/A
Acute Toxicity/ Chronic Toxicity: (ie LD ₅₀)	N/A

12. ECOLOGICAL INFORMATION

Ecotoxicity:	not classified
Persistence and	not classified
Degradability:	
Mobility:	not classified
Other:	not classified

13. DISPOSAL CONSIDERATIONS

Disposal methods: (including container disposal) This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point. Disposal should be in accordance with local, state or national legislation

Special precautions for landfill or incineration:

Brand & Product Name: ACRYLIC BINDER 235G, ACRYLBINDER 470G		
Product Code:	7029.160, 7029.161	
Page 7 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

14. TRANSPORT INFORMATION

ROAD & RAIL TRANSPORT:	Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road and rail.
UN Number: UN Proper Shipping Name: D.G. Class: Subsidiary Risk: Packaging Group: HAZCHEM Code: Segregation:	N/A N/A N/A N/A N/A N/A
Special Precautions For User:	
MARINE TRANSPORT:	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN Number: UN Proper Shipping Name: D.G. Class: Subsidiary Risk: Packaging Group: Stowage & Segregation:	N/A N/A N/A N/A N/A
Special Precautions For User:	
AIR TRANSPORT:	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) for transport by air.
UN Number: UN Proper Shipping Name: D.G. Class: Subsidiary Risk: Packaging Group: Special Precautions For User:	N/A N/A N/A N/A

DG ERG Code: N/A

Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G	
Product Code:	7029.160, 7029.161	
Page 8 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015

15. REGULATORY INFORMATION

Poisons Schedule: APVMA Status: TGA Status: AICS Status: AQIS Status: ADG Status: NOHSC Status: Other:

All the constituents of this product are listed on AICS

16. OTHER INFORMATION.

MSDS Issue date:March 10, 2015Issue Number:20150306

Reason for issue:

In any event, the review and, if necessary, the re-issue of this MSDS shall be no longer than 5 years after the last date of issue.

The Safety Data	nd environmental regulations/legislation specific for the substance or mixture Sheet is compiled according to the current European requirements. amendment of the aerosol dispenser directive 75/324/EEC. 45/EC
Regulation (EC)	No 1907/2006 (REACH)Australian Inventory of Chemical Substances
DG ERG Code	Dangerous Goods Emergency Response Guidebook Code. The Emergency Response Guidebook is used by first responders (eg firefighters, police officers and ambulance personnel) when responding to a transportation emergency involving hazardous materials.
LD ₅₀	The median lethal toxicological dose, LD_{50} is an abbreviation for "Lethal Dose, 50%". of a toxic substance. This is the dose required to kill half the members of a tested population.
MSDS	Material Safety Data Sheet Short Term Exposure Limit - A 15 minute TWA exposure which should not be exceeded at any time during a working day even if the eight-hour TWA average is within the TWA exposure standard. Exposures at the STEL should not be longer than 15 minutes and should not be repeated more than four times per day. There
STEL	should be at least 60 minutes between successive exposures at the STEL.
TGA	Therapeutic Goods Administration Threshold Limit Value - TLV is a proprietary name registered by the American Conference of Governmental Industrial Hygienists (ACGIH) and refers to airborne
TLV	concentrations of substances or levels of physical agents to which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. Time Weighted Average - The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day
TWA	working week. UN numbers are four-digit numbers that identify hazardous substances, and articles (such as explosives, flammable liquids, toxic substances, etc.) in the framework of
UN Number	international transport.

Literature References: Sources of Data:

Brand & Product Name:	ACRYLIC BINDER 235G, ACRYLBINDER 470G	
Product Code:	7029.160, 7029.161	
Page 9 of 8	Issue Number: 20150306	Issue Date: Mar., 10,2015